

Thread Restorer N7280 ®



Specially reinforce design to repair large threads in the given diameter range. No prior thread measurement is needed. Quickly adjust to any thread diameter & pitch. Applicable standards - inch, metric, LH, RH, coarse & fine. A major advantage over taps – can enter below damaged grooves. Automatically chases good thread sections to repair the damaged parts. The cutting Blade made of HSS (62RC) – Guided by the undamaged thread to re groove the damaged section. Removes rust and burrs. Recommended for large internal threads in oil & gas production & pipelines, mining Industry, large truck & heavy soil moving equipment, large production machinery.



	Ø D Range	Pipes	L	B	H	ROD	ØR	ØR	Package Size			Weight	
									L	W	H	Lb	gm
Inch	3 ¹ / ₄ - 3 ³ / ₄	2 ³ / ₄ - 3 ¹ / ₄	6 ⁷ / ₁₆	1 ¹⁵ / ₁₆	4 ⁵ / ₈	7 ⁹ / ₁₆	2 ¹ / ₈	3 ¹ / ₄	10 ⁵ / ₈	10	2 ⁷ / ₈	3.2	1460
mm	82-95		163	50	118	192	54	82	270	255	73		

Cat. No	Part Name	Part No.	Size	Description
07280	RK 26 60°C	07266	82 - 95 mm	Fitted as standard
	RK 26 60°F	07268	3 1/4" – 3 3/4"	For threads finer than 14 TPI or 1.75mm
	RK 26 55°C	07265		Comply to British standard threads
	RK 26 55°F	07262	For threads finer than 14 TPI or 1.75mm	